



Artikelnummer	Bruchkraft		zulässiger Kettenzug	Gelenkfläche a _k	rechnerisch k _s	rechnerische Gelenkflächenpressung		Teilung P	lichte Weite b ₁	Bolzen Ø d ₁	Buchsen Ø d ₂	Rollen Typ B d ₃	Rollen Typ C d ₄	Rollen Typ D		Laschen						Gewicht kg/m
	FB min. (N)	(N)				pi (N/mm ²)	d ₅ (mm)							d ₆ (mm)	b ₂ (mm)	b ₃ (mm)	s/s ₁ (mm)	h ₁ (mm)	h ₂ (mm)	h ₃ (mm)		
																					(mm)	
FV180A100	180.000	30.000	1.220	6	24,6	100	45,0	20,0	30,0					43,0	50,0	8,0	50,0				12,5	
FV180B100	180.000	30.000	1.220	6	24,6	100	45,0	20,0		42,0				43,0	50,0	8,0	50,0				15,0	
FV180C100	180.000	30.000	1.220	6	24,6	100	45,0	20,0				70,0		43,0	50,0	8,0	50,0				18,0	
FV180E100	180.000	30.000	1.220	6	24,6	100	45,0	20,0				70,0		43,0	50,0	8,0		70,0	45,0		26,7	
FV180A125	180.000	30.000	1.220	6	24,6	125	45,0	20,0	30,0					43,0	50,0	8,0	50,0				10,8	
FV180B125	180.000	30.000	1.220	6	24,6	125	45,0	20,0		42,0				43,0	50,0	8,0	50,0				12,6	
FV180C125	180.000	30.000	1.220	6	24,6	125	45,0	20,0				70,0		43,0	50,0	8,0	50,0				19,2	
FV180D125	180.000	30.000	1.220	6	24,6	125	45,0	20,0					100,0	120,0	43,0	50,0	8,0	50,0				31,4
FV180E125	180.000	30.000	1.220	6	24,6	125	45,0	20,0				70,0		43,0	50,0	8,0		70,0	45,0		23,1	
FV180A160	180.000	30.000	1.220	6	24,6	160	45,0	20,0	30,0					43,0	50,0	8,0	50,0				9,8	
FV180B160	180.000	30.000	1.220	6	24,6	160	45,0	20,0		42,0				43,0	50,0	8,0	50,0				11,2	
FV180C160	180.000	30.000	1.220	6	24,6	160	45,0	20,0				70,0		43,0	50,0	8,0	50,0				16,4	
FV180D160	180.000	30.000	1.220	6	24,6	160	45,0	20,0					100,0	120,0	43,0	50,0	8,0	50,0				25,9
FV180E160	180.000	30.000	1.220	6	24,6	160	45,0	20,0				70,0		43,0	50,0	8,0		70,0	45,0		20,0	
FV180A200	180.000	30.000	1.220	6	24,6	200	45,0	20,0	30,0					43,0	50,0	8,0	50,0				9,1	
FV180B200	180.000	30.000	1.220	6	24,6	200	45,0	20,0		42,0				43,0	50,0	8,0	50,0				10,2	
FV180C200	180.000	30.000	1.220	6	24,6	200	45,0	20,0				70,0		43,0	50,0	8,0	50,0				14,3	
FV180D200	180.000	30.000	1.220	6	24,6	200	45,0	20,0					100,0	120,0	43,0	50,0	8,0	50,0				22,0
FV180E200	180.000	30.000	1.220	6	24,6	200	45,0	20,0				70,0		43,0	50,0	8,0		70,0	45,0		17,7	
FV180A250	180.000	30.000	1.220	6	24,6	250	45,0	20,0	30,0					43,0	50,0	8,0	50,0				8,5	
FV180B250	180.000	30.000	1.220	6	24,6	250	45,0	20,0		42,0				43,0	50,0	8,0	50,0				9,5	
FV180C250	180.000	30.000	1.220	6	24,6	250	45,0	20,0				70,0		43,0	50,0	8,0	50,0				12,7	
FV180D250	180.000	30.000	1.220	6	24,6	250	45,0	20,0					100,0	120,0	43,0	50,0	8,0	50,0				18,9
FV180E250	180.000	30.000	1.220	6	24,6	250	45,0	20,0				70,0		43,0	50,0	8,0		70,0	45,0		15,9	
FV180A315	180.000	30.000	1.220	6	24,6	315	45,0	20,0	30,0					43,0	50,0	8,0	50,0				8,2	
FV180B315	180.000	30.000	1.220	6	24,6	315	45,0	20,0		42,0				43,0	50,0	8,0	50,0				8,9	
FV180C315	180.000	30.000	1.220	6	24,6	315	45,0	20,0				70,0		43,0	50,0	8,0	50,0				11,6	
FV180D315	180.000	30.000	1.220	6	24,6	315	45,0	20,0					100,0	120,0	43,0	50,0	8,0	50,0				14,5
FV180A400	180.000	30.000	1.220	6	24,6	400	45,0	20,0	30,0					43,0	50,0	8,0	50,0				7,6	
FV180B400	180.000	30.000	1.220	6	24,6	400	45,0	20,0		42,0				43,0	50,0	8,0	50,0				8,2	
FV180C400	180.000	30.000	1.220	6	24,6	400	45,0	20,0				70,0		43,0	50,0	8,0	50,0				10,3	
FV180D400	180.000	30.000	1.220	6	24,6	400	45,0	20,0					100,0	120,0	43,0	50,0	8,0	50,0				12,6
FV180HTH	234.000	30.000	1.220	8	24,6		45,0	20,0	30,0													