



Artikelnummer	Bruchkraft	zulässiger Kettenzug	Gelenkfläche	rechnerisch	rechnerische Gelenkflächenpressung	Teilung	lichte Weite	Bolzen Ø	Buchsen Ø	Rollen Typ B	Rollen Typ C	Rollen Typ D			Laschen						Gewicht
	FB min.		a _k	k ₃	p _i		P					b ₁	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	b ₂	b ₃	
	(N)	(mm ²)	(mm)	(N/mm ²)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	
M112A80	112.000	16.000	660	7	24,2	80	32	15,0	21,0					33,0	38,0	6	40				6,7
M112B80	112.000	16.000	660	7	24,2	80	32	15,0		30				33,0	38,0	6	40				7,7
M112C80	112.000	16.000	660	7	24,2	80	32	15,0			60			33,0	38,0	6	40				14,0
M112D80	112.000	16.000	660	7	24,2	80	32	15,0				70	22,0	33,0	38,0	6	40				14,6
M112E80	112.000	16.000	660	7	24,2	80	32	15,0			60			33,0	38,0	6		60	40		9,7
M112A100	112.000	16.000	660	7	24,2	100	32	15,0	21,0					33,0	38,0	6	40				6,1
M112B100	112.000	16.000	660	7	24,2	100	32	15,0		30				33,0	38,0	6	40				6,9
M112C100	112.000	16.000	660	7	24,2	100	32	15,0			60			33,0	38,0	6	40				11,9
M112D100	112.000	16.000	660	7	24,2	100	32	15,0				70	22,0	33,0	38,0	6	40				12,4
M112E100	112.000	16.000	660	7	24,2	100	32	15,0			60			33,0	38,0	6		60	40		14,0
M112A125	112.000	16.000	660	7	24,2	125	32	15,0	21,0					33,0	38,0	6	40				5,6
M112B125	112.000	16.000	660	7	24,2	125	32	15,0		30				33,0	38,0	6	40				6,3
M112C125	112.000	16.000	660	7	24,2	125	32	15,0			60			33,0	38,0	6	40				10,3
M112D125	112.000	16.000	660	7	24,2	125	32	15,0				70	22,0	33,0	38,0	6	40				10,7
M112E125	112.000	16.000	660	7	24,2	125	32	15,0			60			33,0	38,0	6		60	40		12,3
M112A160	112.000	16.000	660	7	24,2	160	32	15,0	21,0					33,0	38,0	6	40				5,2
M112B160	112.000	16.000	660	7	24,2	160	32	15,0		30				33,0	38,0	6	40				5,8
M112C160	112.000	16.000	660	7	24,2	160	32	15,0			60			33,0	38,0	6	40				8,9
M112D160	112.000	16.000	660	7	24,2	160	32	15,0				70	22,0	33,0	38,0	6	40				9,2
M112E160	112.000	16.000	660	7	24,2	160	32	15,0			60			33,0	38,0	6		60	40		10,9
M112A200	112.000	16.000	660	7	24,2	200	32	15,0	21,0					33,0	38,0	6	40				5,0
M112B200	112.000	16.000	660	7	24,2	200	32	15,0		30				33,0	38,0	6	40				5,4
M112C200	112.000	16.000	660	7	24,2	200	32	15,0			60			33,0	38,0	6	40				8,1
M112D200	112.000	16.000	660	7	24,2	200	32	15,0				70	22,0	33,0	38,0	6	40				8,4
M112A250	112.000	16.000	660	7	24,2	250	32	15,0	21,0					33,0	38,0	6	40				4,7
M112B250	112.000	16.000	660	7	24,2	250	32	15,0		30				33,0	38,0	6	40				5,1
M112C250	112.000	16.000	660	7	24,2	250	32	15,0			60			33,0	38,0	6	40				7,2
M112D250	112.000	16.000	660	7	24,2	250	32	15,0				70	22,0	33,0	38,0	6	40				7,5
M112A315	112.000	16.000	660	7	24,2	315	32	15,0	21,0					33,0	38,0	6	40				4,5
M112B315	112.000	16.000	660	7	24,2	315	32	15,0		30				33,0	38,0	6	40				4,8
M112C315	112.000	16.000	660	7	24,2	315	32	15,0			60			33,0	38,0	6	40				6,5
M112D315	112.000	16.000	660	7	24,2	315	32	15,0				70	22,0	33,0	38,0	6	40				6,7
M112A400	112.000	16.000	660	7	24,2	400	32	15,0	21,0					33,0	38,0	6	40				4,4
M112B400	112.000	16.000	660	7	24,2	400	32	15,0		30				33,0	38,0	6	40				4,6
M112C400	112.000	16.000	660	7	24,2	400	32	15,0			60			33,0	38,0	6	40				5,9
M112D400	112.000	16.000	660	7	24,2	400	32	15,0				70	22,0	33,0	38,0	6	40				6,1