



Artikelnummer	Bruchkraft	zulässiger Kettenzug	Gelenkfläche a <sub>k</sub>	rechnerisch k <sub>3</sub>	rechnerische Gelenkflächenpressung p <sub>i</sub>	Teilung P	lichte Weite b <sub>1</sub>	Bolzen Ø d <sub>1</sub>	Buchsen Ø d <sub>2</sub>	Rollen Typ B d <sub>3</sub>	Rollen Typ C d <sub>4</sub>	Rollen Typ D		Laschen						Gewicht kg/m								
	FB min.											(N)	(mm <sup>2</sup> )	(N/mm <sup>2</sup> )	(mm)	(mm)	(mm)	(mm)	(mm)		(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
	(N)											(N)	(mm <sup>2</sup> )	(N/mm <sup>2</sup> )	(mm)	(mm)	(mm)	(mm)	(mm)		(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
M224A100	224.000	32.000	1.239	7	25,8	100	43	21,0	30,0					44,0	49,0	8	60				14,0							
M224B100	224.000	32.000	1.239	7	25,8	100	43	21,0		42				44,0	49,0	8	60				15,7							
M224A125	224.000	32.000	1.239	7	25,8	125	43	21,0	30,0					44,0	49,0	8	60				1,8							
M224B125	224.000	32.000	1.239	7	25,8	125	43	21,0		42				44,0	49,0	8	60				14,5							
M224C125	224.000	32.000	1.239	7	25,8	125	43	21,0			85			44,0	49,0	8	60				25,6							
M224D125	224.000	32.000	1.239	7	25,8	125	43	21,0				100	30,0	44,0	49,0	8	60				26,8							
M224A160	224.000	32.000	1.239	7	25,8	160	43	21,0	30,0					44,0	49,0	8	60				11,6							
M224B160	224.000	32.000	1.239	7	25,8	160	43	21,0		42				44,0	49,0	8	60				13,0							
M224C160	224.000	32.000	1.239	7	25,8	160	43	21,0			85			44,0	49,0	8	60				21,6							
M224D160	224.000	32.000	1.239	7	25,8	160	43	21,0				100	30,0	44,0	49,0	8	60				22,6							
M224A200	224.000	32.000	1.239	7	25,8	200	43	21,0	30,0					44,0	49,0	8	60				10,8							
M224B200	224.000	32.000	1.239	7	25,8	200	43	21,0		42				44,0	49,0	8	60				11,9							
M224C200	224.000	32.000	1.239	7	25,8	200	43	21,0			85			44,0	49,0	8	60				18,8							
M224D200	224.000	32.000	1.239	7	25,8	200	43	21,0				100	30,0	44,0	49,0	8	60				19,6							
M224A250	224.000	32.000	1.239	7	25,8	250	43	21,0	30,0					44,0	49,0	8	60				10,2							
M224C250	224.000	32.000	1.239	7	25,8	250	43	21,0		42				44,0	49,0	8	60				11,0							
M224C250	224.000	32.000	1.239	7	25,8	250	43	21,0			85			44,0	49,0	8	60				16,6							
M224D250	224.000	32.000	1.239	7	25,8	250	43	21,0				100	30,0	44,0	49,0	8	60				17,2							
M224A315	224.000	32.000	1.239	7	25,8	315	43	21,0	30,0					44,0	49,0	8	60				9,8							
M224B315	224.000	32.000	1.239	7	25,8	315	43	21,0		42				44,0	49,0	8	60				10,5							
M224C315	224.000	32.000	1.239	7	25,8	315	43	21,0			85			44,0	49,0	8	60				15,1							
M224D315	224.000	32.000	1.239	7	25,8	315	43	21,0				100	30,0	44,0	49,0	8	60				15,7							
M224A400	224.000	32.000	1.239	7	25,8	400	43	21,0	30,0					44,0	49,0	8	60				9,3							
M224B400	224.000	32.000	1.239	7	25,8	400	43	21,0		42				44,0	49,0	8	60				9,9							
M224C400	224.000	32.000	1.239	7	25,8	400	43	21,0			85			44,0	49,0	8	60				13,5							
M224D400	224.000	32.000	1.239	7	25,8	400	43	21,0				100	30,0	44,0	49,0	8	60				13,9							
M224A500	224.000	32.000	1.239	7	25,8	500	43	21,0	30,0					44,0	49,0	8	60				9,0							
M224B500	224.000	32.000	1.239	7	25,8	500	43	21,0		42				44,0	49,0	8	60				9,4							
M224C500	224.000	32.000	1.239	7	25,8	500	43	21,0			85			44,0	49,0	8	60				12,3							
M224D500	224.000	32.000	1.239	7	25,8	500	43	21,0				100	30,0	44,0	49,0	8	60				12,6							
M224A630	224.000	32.000	1.239	7	25,8	630	43	21,0	30,0					44,0	49,0	8	60				8,7							
M224B630	224.000	32.000	1.239	7	25,8	630	43	21,0		42				44,0	49,0	8	60				9,0							
M224C630	224.000	32.000	1.239	7	25,8	630	43	21,0			85			44,0	49,0	8	60				11,3							
M224D630	224.000	32.000	1.239	7	25,8	630	43	21,0				100	30,0	44,0	49,0	8	60				11,6							
<b>M224HTH</b>	<b>290.000</b>	32.000	1.239	<b>9</b>	25,8																							