



Artikelnummer	Bruchkraft	zulässiger Kettenzug	Gelenkfläche a _k	rechnerisch k ₃	rechnerische Gelenkflächenpressung p _i	Teilung P	lichte Weite b ₁	Bolzen Ø d ₁	Buchsen Ø d ₂	Rollen Typ B d ₃	Rollen Typ C d ₄	Rollen Typ D		Laschen						Gewicht kg/m	
	FB min. (N)											d ₅	d ₆	b ₂	b ₃	s/s ₁	h ₁	h ₂	h ₃		
M80A80	80.000	11.400	456	7	25,0	80	28	12,0	18,0					29,0	33,0	5	35				4,5
M80B80	80.000	11.400	456	7	25,0	80	28	12,0		25				29,0	33,0	5	35				5,2
M80C80	80.000	11.400	456	7	25,0	80	28	12,0			50			29,0	33,0	5	35				9,0
M80D80	80.000	11.400	456	7	25,0	80	28	12,0				60	20,0	29,0	33,0	5	35				9,5
M80E80	80.000	11.400	456	7	25,0	80	28	12,0			50			29,0	33,0	5		50	32,5		6,4
M80A100	80.000	11.400	456	7	25,0	100	28	12,0	18,0					29,0	33,0	5	35				4,2
M80B100	80.000	11.400	456	7	25,0	100	28	12,0		25				29,0	33,0	5	35				4,7
M80C100	80.000	11.400	456	7	25,0	100	28	12,0			50			29,0	33,0	5	35				7,8
M80D100	80.000	11.400	456	7	25,0	100	28	12,0				60	20,0	29,0	33,0	5	35				8,1
M80E100	80.000	11.400	456	7	25,0	100	28	12,0			50			29,0	33,0	5		50	32,5		9,1
M80A125	80.000	11.400	456	7	25,0	125	28	12,0	18,0					29,0	33,0	5	35				3,9
M80B125	80.000	11.400	456	7	25,0	125	28	12,0		25				29,0	33,0	5	35				4,3
M80C125	80.000	11.400	456	7	25,0	125	28	12,0			50			29,0	33,0	5	35				6,8
M80D125	80.000	11.400	456	7	25,0	125	28	12,0				60	20,0	29,0	33,0	5	35				7,1
M80E125	80.000	11.400	456	7	25,0	125	28	12,0			50			29,0	33,0	5		50	32,5		8,0
M80A160	80.000	11.400	456	7	25,0	160	28	12,0	18,0					29,0	33,0	5	35				3,7
M80B160	80.000	11.400	456	7	25,0	160	28	12,0		25				29,0	33,0	5	35				4,0
M80C160	80.000	11.400	456	7	25,0	160	28	12,0			50			29,0	33,0	5	35				5,9
M80D160	80.000	11.400	456	7	25,0	160	28	12,0				60	20,0	29,0	33,0	5	35				6,1
M80E160	80.000	11.400	456	7	25,0	160	28	12,0			50			29,0	33,0	5		50	32,5		7,1
M80A200	80.000	11.400	456	7	25,0	200	28	12,0	18,0					29,0	33,0	5	35				3,5
M80B200	80.000	11.400	456	7	25,0	200	28	12,0		25				29,0	33,0	5	35				3,8
M80C200	80.000	11.400	456	7	25,0	200	28	12,0			50			29,0	33,0	5	35				5,4
M80D200	80.000	11.400	456	7	25,0	200	28	12,0				60	20,0	29,0	33,0	5	35				5,6
M80A250	80.000	11.400	456	7	25,0	250	28	12,0	18,0					29,0	33,0	5	35				3,4
M80B250	80.000	11.400	456	7	25,0	250	28	12,0		25				29,0	33,0	5	35				3,6
M80C250	80.000	11.400	456	7	25,0	250	28	12,0			50			29,0	33,0	5	35				4,9
M80D250	80.000	11.400	456	7	25,0	250	28	12,0				60	20,0	29,0	33,0	5	35				5,1
M80A315	80.000	11.400	456	7	25,0	315	28	12,0	18,0					29,0	33,0	5	35				3,2
M80B315	80.000	11.400	456	7	25,0	315	28	12,0		25				29,0	33,0	5	35				3,4
M80C315	80.000	11.400	456	7	25,0	315	28	12,0			50			29,0	33,0	5	35				4,4
M80D315	80.000	11.400	456	7	25,0	315	28	12,0				60	20,0	29,0	33,0	5	35				4,6